

Also available in the self-contained range for "Bistrot" cube: **B 1706, B 2008, B 2608.** B 2615, B 3515, B 4422, B 5522, B 7040, B 9050 B 8040
See pertaining literature for more details







B 9050 AS/WS

Bar Line Equipment range is the newly released EU made ice makers for Thimble-shaped rounded ice cubes coming from Bar Line.

Built in the Italian manufacturing plant of Frimont Spa, ISO 9001 Certified, these units are built with sturdy, corrosion resistant stainless steel, and feature European made componentry to assure maximum quality and reliability. Tested one by one, the Bar Line self contained units feature well balanced ratio between production and storage capacity, alongside with reduced outer dimensions that allow for built-in installations.

Front air louvers assure appropriate airflow in critical install requirements. Contemporary, elegant design unites excellent operational features with the reliability obtained through years of successful experience in ice making technology.

Insulated bin door and ice storage bin minimize air condensation and water formation on equipment surfaces. Electromechanic controls maximise reliability and ease of repair during the entire life of the equipment.

Proudly Made in Italy.


## **2014 FUNCTIONALITY IMPROVEMENTS:**

- Improved water distribution system alongside with evaporator assembly: a larger number of ice cubes are now produced per each cycle, while the newly designed water distribution spray system provides best evaporator surface coverage and is simple to remove during routine cleaning.
- Optimized dimensions and production/ storage ratios. Easier to fit even under lowest bar counters and in reduced footprint spaces.
- Front panel installed thermostatic controls for ice cube size and storage bin ice level sensor. Easily accessible, allow for an easy adjustment of the key working parameters of the machine.
- Bin-door slide rollers for a smooth openclose movement, with door movement rubber, sound dampening, shock absorbers.
- Utilities connection may run through side panel openings, as well as through the base panel, for a reduced depth installation requirement.

BAR

Also available in the self-contained range for "Bistrot" cube: B 1706, B 2008, B 2608, B 2615, B 3515, B 4422, B 5522, B 7040, B 9050 B 8040 See pertaining literature for more details





ORDERING AND SPECIFICATION INFORMATION										
Model No.	Cond. unit	ICE Production per 24 hrs. at 10°C Air/10°C Water kg	ICE Production per 24 hrs. at 21°C Air/15°C Water kg	Bin storage kg	Voltage Characteristics	Refrigerant	Water Consumption I/h*	Electric Consumption kWh/24h*	Net Weight	Max. Shipping Weight kg
B 9050 AS	Air	93	90	50	230/50/1	R404A	9	17,6	58	67
B 9050 WS	Water	96	90	50	230/50/1	R404A	79,1	15,3	58	67

\*measured at 32°C air / 21°C water









Frimont S.p.A.

Via Lainate 31/b - 20010 Pogliano Milanese - (Milano) Italy Tel. +39.02.93960.239 - Fax +39.02.93960.201 barline@frimont.it - www.barline.it